

4MP Network IR PTZ Dome Camera

RS-PT8R26U-36XIPAT



Key Features



- High quality image with 4MP, 1/1.8" CMOS sensor
- 2688*1520@60fps in the main stream
- Ultra 265, H.265, H.264, MJPEG
- Five streams
- 40X Optical Zoom
- Lighthunter technology ensures ultra-high image quality in low illumination environment
- Smart IR, up to 200m IR distance
- Gyroscope stabilization for stable picture
- AC 24V ±25%, DC 24V±25%, PoE++ (IEEE 802.3bt) power supply
- Alarm 2 in and 1 out, Audio 1 in and 1 out
- IP67 ingress protection

Specifications

RS-PT8R26U-36XIPAT					
Camera					
Sensor	1/1.8", 4.0 megapixel, progressive scan, CMOS				
Minimum Illumination	Colour: 0.001Lux (F1.3, AGC ON) 0Lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Shutter	Auto/Manual; shutter time: 1 ~ 1/100000s				
WDR	140dB				
S/N	>56dB				
Lens					
Lens type	5.7 ~ 228mm, AF automaticfocusing and motorized zoom lens				
Digital Zoom	16				
Optical Zoom	40				
Iris	Auto/manual; F1.3 ~ F4.6				
Angle of View (H)	58.5° ~ 2.1°				
Angle of View (V)	34.9° ~ 1.2°				
Angle of View (O)	72.0° ~ 2.5°				
DORI					
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	5.7	103.7(340.1ft)	41.5(136.0ft)	20.7(68.0ft)	10.4(34.0ft)
	228	3249.0(10659.4ft)	1299.6(4263.8ft)	649.8(2131.9ft)	324.9(1065.9ft)
Illuminator					
IR Range	UP to 200m				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Video					
Video Compression	Ultra 265, H.265, H.264, MJPEG				
Frame Rate	Main Stream: 4MP (2688*1520)@60fps; Sub Stream: 2MP (1920*1080)@60fps; Third Stream: D1 (720*576)@60fps; Fourth Stream:D1(720x576)@60fps; Fifth Stream:D1(720x576)@60fps;				
H.264 Type	Baseline Profile/Main Profile/High Profile				
H.265 Type	Main Profile				
U-code	Support				
ROI	Up to 8 areas				
Video stream	Five streams				
OSD	Up to 8 OSDs				
Privacy Mask	Up to 24 areas(Up to 8 blacks or 8 mosaics in the same picture)				
Image					
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital noise reduction	2D/3D DNR				
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise				

EIS	Support (gyroscope)
HLC	Support
BLC	Support
Defog	Optical Defog & Digital Defog
Events	
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio	
Audio Compression	G.711U,G.711A
Audio Bitrate	64 Kbps
Two-way audio	Support
Suppression	Support
Sampling Rate	8KHZ
Storage	
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR,NAS(NFS)
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS
Compatible Integration	ONVIF (Profile S, Profile G,, Profile Q, Profile T), API, SDK
User/Host	Up to 32 users. 2 user levels: administrator and common user
Security	Password protection, strong password, HTTPS encryption, Export operation logs, basic and digest authentication for RTSP, digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
Pan & Tilt	
Pan Range	360° (endless)
Pan Speed	0.1°/s ~ 180°/s
	Preset speed: 300°/s
Tilt Range	-15° ~ 90° (auto reverse)
Tilt Speed	0.1° ~ 180°/s
	Preset speed: 240°/s
Number of Presets	1024
Patrol	Preset patrol, route patrol, recorded patrol
Preset Image Freeze	Support
Home Position	Support
Interface	
Audio I/O	1/1
Alarm I/O	2/1
Serial Port	1 RS485
Built-in Mic	N/A
Built-in Speaker	N/A
WIFI	N/A

Network	1 RJ45 10M / 100M Base-TX Ethernet
Video output	N/A
Certification	
	FCC CE ROHS BIS
General	
Power	AC 24V ±25%, DC 24V ±25%, PoE++ (IEEE 802.3bt) (IEEE802.3bt switch required)
	Power consumption: Max 70W
Power Interface	Wires with cold-pressed terminal
Dimensions (Ø x H)	Φ270 x 496.7mm (Φ10.6" x 19.6")
Weight	9.69kg (21.4lb)
Working Environment	-40°C ~ 70°C (-40°F ~ 158°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-40°C ~ 70°C (-40°F ~ 158°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	6KV
Vandal Resistant	N/A
Ingress Protection	IP67
Reset Button	Support

Dimensions



Accessories

RS-UF45-A-IN



RS-SE45-A-IN



RS-SE45-IN



RS-CE45-IN



RS-JB12-IN



RS-WE45-A-IN



RS-WE45-B-IN






RS-UP08-A/B-IN



RS-UC08-A/B-IN



Pendent Mount	Wall Mount
RS-UF45-A-IN + RS-SE45-A-IN/RS-SE45-IN; RS-CE45-IN;	RS-WE45-A-IN/RS-WE45-B-IN + RS-JB12-IN + RS-UC08-A/B-IN
	
Pole Mount	/
RS-WE45-A-IN/RS-WE45-B-IN + RS-JB12-IN + RS-UP08-A/B-IN	/
	/